

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number  
**WO-2005/076609 A1**

(51) International Patent Classification<sup>7</sup>: H04N-7/00; 7/52

(21) International Application Number:  
PCT/KR2004/002598

(22) International Filing Date: 12 October 2004 (12.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
10-2004-0006990 3 February 2004 (03.02.2004) KR

(71) Applicant (for all designated States except US): LG  
ELECTRONIC INC. [KR/KR]; 20, Yoido-dong, Young-  
dungpo-gu, Seoul 150-721 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): SEO, Kang Soo  
[KR/KR]; 104-1504, Chowon APT., #898, Pyeong-  
chon-dong, Dongan-gu, Anyang-si, Gyeonggi-do 431-075  
(KR). KIM, Byung Jin [KR/KR]; 111-204, Chonggu  
APT., Hansolmaeul, 110, Jeongja-dong, Bundang-gu,  
Seongnam-si, Gyeonggi-do 463-010 (KR). YOO, Jea  
Yong [KR/KR]; 205-808, Ssangyong APT., Garak 2-dong,  
Songpa-gu, Seoul, 138-747 (KR).

(74) Agents: BAHNG, Hae Cheol et al.; KBK & Associates,  
15th Floor Yosam Building, 648-23, Yeoksam-dong, Kang-  
nam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,  
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: TEXT SUBTITLE DECODER AND METHOD FOR DECODING TEXT-SUBTITLE STREAMS



(57) Abstract: A text subtitle decoder (42) includes a text subtitle processor (411), a text renderer (412), and a presentation controller (415). The text subtitle processor (411) parses a text subtitle stream into text data and reproduction control information, where the text data represent a subtitle text to be displayed within a text subtitle region. After the text subtitle stream is parsed, the text renderer (412) renders the text data into bitmap data using the reproduction control information. The presentation controller (415) controls operations of the text subtitle processor (411) and the text renderer (412).

# **TEXT SUBTITLE DECODER AND METHOD FOR DECODING TEXT SUBTITLE STREAMS**

## **Technical Field**

5 The present invention relates to a text subtitle decoder and a method for decoding text subtitle streams recorded in an optical disc.

## **Background Art**

Optical discs are widely used as an optical recording medium for recording mass data.

10 Presently, among a wide range of optical discs, a new high density optical recording medium (HD-DVD), such as the Blu-ray Disc (hereafter referred to as "BD"), is under development for writing and storing high definition video and audio data for a long period of time. Currently, global standard technical specifications of the Blu-ray Disc (BD), which is known to be the next generation HD-DVD technology, are under establishment as a next  
15 generation optical recording solution that is able to have a data significantly surpassing the conventional DVD, along with many other digital apparatuses.

Accordingly, optical reproducing apparatuses having the Blu-ray Disc (BD) standards applied thereto are also being developed. However, since the Blu-ray Disc (BD) standards are yet to be completed, there have been many difficulties in developing a complete optical  
20 reproducing apparatus. Particularly, in order to effectively reproduce the data from the Blu-ray Disc (BD), not only should the main AV data as well as various data required for a

user's convenience, such as subtitle information as the supplementary data related to the main AV data, be provided, but also managing information for reproducing the main data and the subtitle data recorded in the optical disc should be systemized and provided.

However, in the present Blu-ray Disc (BD) standards, since the standards of the supplementary data, particularly the subtitle information, are not completely consolidated, there are many restrictions in the full-scale development of a Blu-ray Disc (BD) basis optical reproducing apparatus. And, such restrictions cause problems in providing the supplementary data such as subtitles to the user.

#### 10 **Disclosure of Invention**

Accordingly, the present invention is directed to a recording medium for reproduction of text subtitle streams, and methods and apparatuses for recording and reproducing the same, all of which substantially obviate one or more problems due to limitations and disadvantages of the related art.

15 An object of the present invention is to define specific reproduction control information in a text subtitle stream such that text data for a text subtitle included in the text subtitle stream could be reproduced in a standardized manner.

Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention.

20 The objectives and other advantages of the invention may be realized and attained by the

structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

In one aspect of the present invention, a text subtitle decoder includes a text subtitle processor, a text renderer, and a presentation controller. The text subtitle processor parses a text subtitle stream into text data and reproduction control information. The text data represents a subtitle text to be displayed within a text subtitle region. The text renderer renders the text data into bitmap data using the reproduction control information, and the presentation controller control operations of the text subtitle processor and the text renderer.

The reproduction control information may include region style information which specifies

a region style of the text subtitle region including an overall font-related style of the text data. The region style of the text subtitle region may be specified by at least one of a region position, a region size, a region background color, a text position, a text flow, a text alignment, a line space, a font identification, a font style, a font size, and a font color defined in the region style information. In addition, the text subtitle processor may further parse the text subtitle stream into inline information for applying a different font-related style to a selected portion of the text data.

In another aspect of the present invention, a method for decoding text subtitle streams recorded in a recoding medium includes the steps of parsing a text subtitle stream into text data and reproduction control information, and rendering the text data into bitmap data using the reproduction control information. The text data represent a subtitle text to be displayed within a text subtitle region. The reproduction control information may include

region style information-specifying a region style of the text subtitle region including an overall font-related style of the text data. The region style of the text subtitle region may be specified by at least one of a region position, a region size, a region background color, a text position, a text flow, a text alignment, a line space, a font identification, a font style, a font size, and a font color defined in the region style information. The above method may further include the step of parsing the text subtitle stream into inline information for applying a different font-related style to a selected portion of the text data.

In a further aspect of the present invention, a system for decoding text subtitle streams recorded on a recording medium includes a text subtitle decoder, a graphics plane, and a color look up table. The text subtitle decoder parses a text subtitle stream into text data and reproduction control information and renders the text data into bitmap data using the reproduction control information. Thereafter, the graphics plane converts the bitmap data into displayable images and the color look up table controls at least one of color and transparency levels of the displayable images.

It is to be understood that both the foregoing general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

#### **Brief Description of The Drawings**

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate

embodiments of the invention and together with the description serve to explain the principle of the invention. In the drawings:

FIG. 1 illustrates an optical (e.g., Blu-ray) disc player according to the present invention;

FIG. 2A illustrates data files recorded in an optical disc according to the present invention;

5 FIG. 2B illustrates data storage areas of an optical disc according to the present invention;

FIGS. 3A and 3B illustrate examples of a text subtitle region displayed on a display screen according to the present invention;

FIG. 4 illustrates an apparatus for decoding AV streams and text subtitle streams according to the present invention;

10 FIG. 5A illustrates an example of a page composition segment (PCS) information included in a text subtitle stream according to the present invention;

FIG. 5B illustrates an example of an object definition segment (ODS) information included in a text subtitle stream according to the present invention;

FIGS. 6A to 6D illustrate several examples of the text subtitle decoder shown in FIG. 4 according to the present invention; and

15 FIG. 7 illustrates an apparatus of recording and/or reproducing text subtitle streams according to the present invention.

#### **Best Mode for Carrying Out the Invention**

20 Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the

same reference numbers will be used throughout the drawings to refer to the same or like parts.

In this description, main data represent audio/video (AV) data that are recorded on an optical disc by an author and belong to a title (e.g., a movie title). In general, the AV data are recorded in MPEG2 format and are often called AV streams or main AV streams. In addition, supplementary data represent all other data associated with reproduction of the main data, examples of which are text subtitle streams, graphic streams, menu information, and supplementary audio streams (e.g., for a browsable slideshow). These supplementary data streams may be recorded in MPEG2 format or any other data format, and they could be multiplexed with the AV streams or exist as independent data files in a same or different data area within the optical disc.

According to the present invention, a subtitle represents caption information for images being reproduced and is often represented in a predetermined language. For example, when a user selects an option for viewing one of a plurality of subtitles for multiple languages while viewing images on display screen, caption information corresponding to the selected option is displayed on a predetermined portion of the display screen. The caption information may be recorded in an optical disc as MPEG2 transport packets, bitmap graphics, or text data. When the caption information is text data, the subtitle is called a text subtitle. A text subtitle stream includes text data for a text subtitle and reproduction control information for the text data. According to one example the present invention, a text subtitle

stream may be recorded in an optical disc and exist as an independent stream file. In addition, the text subtitle stream may be downloaded from an external data source.

FIG. 1 illustrates an optical disc player 1 according to the present invention. The disc player 1 is able to reproduce text subtitle streams and audio/video (AV) streams recorded in an optical disc, an example of which is a Blu-ray disc. Also, the disc player 1 is also able to record text subtitle streams and AV streams on an optical disc.

In addition, the disc player 1 according to the present invention is able to receive or download input data from an external data source, examples of which are a digital television

broadcasting station and the Internet server. After the disc player 1 performs the required

data-processes for the input data, it displays the processed signals on a display device 2 coupled to the disc player 1. Therefore, the disc player 1 is able to receive AV streams and text subtitle streams from the optical disc or the external data source, respectively, and to reproduce AV streams and the text subtitle data simultaneously. The text subtitle data may be in MPEG format, text, XML, or HTML format.

FIG. 2A illustrates data files recorded in a Blu-ray (BD) disc according to the present invention. Referring to FIG. 2A, at least one BD directory (BDMV) is included in a root directory (root). Each BD directory includes an index file (e.g., index.bdmv) and an object file (e.g., MovieObject.bdmv), which represent general files that are used when interacting with one or more users. For example, the index file contains data representing an index table which includes various information regarding a plurality of selectable menus and titles.



Each BD directory includes three file directories including data to be reproduced, and information required for reproducing the data. The file directories included in each BD directory are a stream directory (STREAM), a playlist directory (PLAYLIST), and a clip information directory (CLIPINF).

- 5 The stream directory includes audio/video (AV) stream files and supplementary stream files including one or more text subtitle stream files. The main AV streams and the text subtitle streams may be in the form of MPEG2 transport packets and be named as "\*.m2ts", as shown in FIG. 2A. The text subtitle stream files exist as independent stream files within the stream directory. In addition, the text subtitle stream files could be in other data format and
- 10 be named according to their data format. For example, if the text subtitle stream files are in text format, they could be named as "\*.txt."

Next, the clip information directory includes clip information files (\*.clpi) that correspond to the AV and text subtitle stream files included in the stream directory. A clip information file includes property information and timing information of a corresponding stream file,

- 15 where timing information includes mapping information that maps presentation time stamp (PTS) with source packet number (SPN) using entry point map. In the industry standard, each pair of a stream file and its corresponding clip information file is designated as a clip. For example, 01000.clpi included in CLIPINF includes the property and timing information of 01000.m2ts included in STREAM, and 01000.clpi and 01000.m2ts form a clip.

- 20 Referring back to FIG. 2A, the playlist directory includes one or more PlayList files (\*.mpls), wherein each PlayList file includes at least one PlayItem which designates at least

one main AV clip and the reproduction time for the main AV clip. More specifically, a PlayItem includes information designating beginning and ending times (In-Time and Out-Time) for reproduction of a main AV clip, which may be designated by Clip\_Information\_File\_Name within the PlayItem. Therefore, a PlayList file represents the basic reproduction control information for one or more main AV clips. In addition, the PlayList file may further includes a SubPlayItem, which is the basic reproduction control information of one or more text subtitle stream files. When a SubPlayItem is included in a PlayList file to reproduce one or more text subtitle streams, the SubPlayItem is often synchronized with PlayItem(s) also included in the PlayList file. In addition, when the SubPlayItem is used to reproduce a browsable slideshow, it may not be synchronized with the PlayItem(s).

FIG. 2B illustrates data storage areas of an optical disc, in which the data files shown in FIG. 2A are recorded. As shown in the figure, the disc volume includes a file system information area occupying the inmost portion of the disc volume, a stream area occupying the outmost portion of the disc volume, and a database area occupied between the file system information area and the stream data area. In the file system information area, system information for managing the entire data files is recorded. Next, AV streams and one or more text subtitle streams are prerecorded in the stream area. The general files, PlayList files, and clip information files are recorded in the database area of the disc volume. As discussed above, the general files include an index file and an object file, and the PlayList files and clip information files include information required to reproduce the AV streams

and text subtitle streams recorded in the stream area. A user is able to select a specific playback mode and to reproduce desired main and supplemental streams in the selected playback mode using the information stored in the database area and/or stream area.

FIGs. 3A and 3B illustrate examples of a text subtitle displayed on a display screen 2 according to the present invention. A text subtitle stream recorded on an optical disc includes data representing a subtitle text (e.g., characters). When the text subtitle stream is reproduced, a text subtitle region including the text data is displayed on the display screen 2, as shown in both figures. The text data included within the text subtitle region shown in FIG.

~~3A is in Korean, and the text data displayed within the region shown in FIG. 3B is in~~

English. In order to support both languages, there are more than one independent text subtitle files recorded in the optical disc.

In conclusion, one or more text subtitle streams according to the present invention may be provided from an optical disc, in which the text subtitle streams exist as one or more text subtitle stream files. Or, they could be provided from an external data source, as shown in

FIG. 1. The text subtitle streams may be in MPEG format or any other data format (e.g., text format).

FIG. 4 illustrates an apparatus of decoding AV streams and text subtitle streams according to the present invention. The apparatus includes a packet identifier (PID) filter 5 for separating input streams into video streams, audio streams, graphic streams, and text subtitle streams based on their packet identifiers, an audio decoding part 10 for decoding the audio streams, a video decoding part 20 for decoding the video streams, a graphic decoding

part decoding the graphic streams, and a text subtitle decoding part 40 for decoding the text subtitle streams.

The text subtitle streams may be extracted from an optical disc, or they could be inputted from an external data source. For this reason, the apparatus shown in FIG. 4 includes a switch 6 which selects a data source. For example, if a text subtitle stream in MPEG format is extracted from the optical disc, the switch 6 selects data line A connected to the PID filter 5. On the other hand, if a text subtitle stream in other format (e.g., text, XML, or HTML format) is inputted through the external source, the switch 6 selects data line B which is connected to the external source.

Each of the audio decoding part 10, video decoding part 20, and graphic decoding part 30 includes a transport buffer 11, 21, and 31 for storing a predetermined size of data streams to be decoded. A video plane 23 and a graphics plane 33 are included in the video decoding part 20 and the graphic decoding part 30, respectively, for converting decoded signals into displayable images. The graphic decoding part 30 further includes a color look up table (CLUT) 34 for controlling color and transparency levels of the displayable images.

When the text subtitle decoding part 40 receives one or more text subtitle streams from the switch 6, all of these streams are initially preloaded into a subtitle preloading buffer (SPB) 41 at once. Assuming a typical size of a text subtitle stream file for a single language is about 0.5 megabytes, the size of the subtitle preloading buffer 41 should be greater than 0.5 megabytes. In order to ensure seamless presentation of a text subtitle when a user switches among subtitle stream files supporting multi-languages, the size of the subtitle preloading

buffer 41 should be determined based on the a total number of the text subtitle stream files.

The buffer size must be large enough to preload all the required text subtitle stream files at once. Since all the text subtitle stream files are preloaded into the subtitle preloading buffer 41, extraction and use of the text subtitle streams can be done in a time-efficient manner.

5- Also, the control of the subtitle preloading buffer 41 could be quite simple due to the reason set forth.

The text subtitle decoding part 40 further includes a text subtitle (TXT\_ST) decoder 42 which decodes one or more text subtitle streams stored in the subtitle preloading buffer 41,

a graphics plane 43 for converting the decoded subtitle stream(s) into displayable images,

10 and a color look up table (CLUT) 44 for controlling the color and transparency levels of the converted images.

An image superimposition part 50 included in the apparatus shown in FIG. 4 combines the images outputted from the video decoding part 20, the graphic decoding part 30, and the text subtitle decoding part 40. These combined images are displayed on a display screen.

15 The video images outputted from the video plane 23 of the video decoding part 20 are displayed as a background of the display screen, and the images outputted from the graphic decoding part 30 and/or the text subtitle decoding part 40 are superimposed over the displayed video images. For example, if the output images of the graphic decoding part 30 are interactive graphic images, the text subtitle images outputted from the text subtitle  
20 decoding part 40 are initially superimposed over the video images by a first adder 52.

Thereafter, the interactive graphic images are further superimposed over the subtitle-

superimposed images by a second adder 53. On the other hand, if the output images of the graphic decoding part 30 are presentation graphic images, these images are initially superimposed over the video images from the video decoding part 20 by the first adder 52, and the text subtitle images from the text subtitle decoding part 40 are further superimposed over the video images by the second adder 53.

The apparatus shown in FIG. 4 further includes a system decoder 4 for decoding input data streams extracted from an optical disc, and a microprocessor 3 for controlling operations of all the mentioned components of the apparatus.

Reference will now be made in detail to specific information/data included in a text subtitle

stream according to the present invention. A text subtitle stream file recorded on an optical disc according to the present invention includes a page composition segment (PCS) information including region (global) style information, and an object definition segment (ODS) information including data representing a subtitle text (e.g., characters) and inline (local) style information. When the text subtitle stream file is reproduced, a text subtitle region including the subtitle text is displayed on a display screen according to the region style information and the inline style information.

An example of the page composition segment (PCS) information is illustrated in FIG. 5A.

An object defined in the PCS information represents a text subtitle region (page) and an entire portion of the text included in the text subtitle region. The PCS information includes

object composition information (composition\_object (\*)) including object identification (object\_id), object position information (object\_position\_info), and object cropping

information (object\_cropping\_info) for an object. The PCS information further includes information specifying a style of the text subtitle region displayed within the display screen, and this information is often denoted as region style information or global style information (global style\_page shown in FIG. 5A). For simplicity, it will be referred to as region style information.

The region style information specifies a region style of a text subtitle region including a subtitle text, where the region style includes an overall font-related style of the subtitle text included within the text subtitle region. For example, the region style information specifies the region style by defining a plurality of display properties required for displaying the text

subtitle region including subtitle text on the display screen. For example, the region style information may define a region position (region\_position) indicating at least one of the horizontal and vertical positions of the text subtitle region from an origin of the display screen, a region size (region\_size) indicating at least one of a width and height of the text subtitle region, and a region background color (region\_background\_color) indicating a

background color of the text subtitle region. The region style information may further define a text position (text\_position) indicating a position of the text data within the text subtitle region, a text flow (text\_flow) indicating at least one a character progression (left-to-right or right-to-left) and a line progression (top-to-bottom or bottom-to-top) of the text data within the text subtitle region, a text alignment (text\_alignment) indicating one of left, center, right

alignment of the text data within the text subtitle region, a line space (line\_space) indicating

a distance between two adjacent baselines of the text data within the text subtitle region.

The region style information could also define other display properties not mentioned above.

The region style information further specifies the region style by defining an overall font-related style (font-related display properties) of the subtitle text included in a text subtitle

5 region. For example, the region style information may further define a font identification

(font\_id) indicating a value specifying a font file associated with the text subtitle stream file

including the region style information, a font style (font\_style) indicating at least one

normal, bold, and italic font styles, a font size (font\_size) indicating a vertical size of the

text included in the text subtitle region (e.g., a character), and a font color (font\_color)

10 indicating a color of the text. As described above, the overall font-related style of the

subtitle text within the text subtitle region is specified by at least one of the font

identification, font style, font size, and font color defined in the region style information.

FIG. 5B illustrates an example of the object definition segment (ODS) information included

in a text subtitle stream. An object defined by object identification (object\_id) in the ODS

15 information represents a selected portion of a subtitle text (e.g., characters) included in a

text subtitle region. The ODS information includes object information including object

identification (object\_id) and object version information (object\_version\_number) for an

object. The ODS information further include information for applying a different font-

related style to a selected portion of the text included in a text subtitle, and this information

20 is often denoted as inline style information or local style information (local style\_object

shown in FIG. 5B). For simplicity, it will be referred to as inline style information.



An object of the local style information is to apply a different font-related style for a selected portion of the text included in a text subtitle region. In other words, the local style information specifies a specific font-related style of the selected text portion, which may be different from the overall font-related style defined by the region style information. For example, the inline style information specifies the specific font-related style by redefining at least one of a font identification (font\_id) indicating a value specifying a different font file associated with the text subtitle stream, a font style (font\_style) indicating a different font style, a font size (font\_size) indicating a different font size, and a font color (font\_color) indicating a different font color for the selected text portion within the text subtitle region.

10 In addition, the inline style information may further define various other font-related display properties not mentioned above.

Referring back to FIG. 5B, the ODS information further includes data (Text\_data) representing a subtitle text included in a text subtitle region. This text data may be included object data information (Object\_Data), which is included in object\_data\_fragment, as

15 shown in FIG. 5B. However, the text data may be included in the ODS in other manner.

A text subtitle stream file may further include palette information for use with a color look up table (CLUT). This palette information may be included in palette definition-segment (PDS) information further included in the text subtitle stream file, or it may be included in a clip information file corresponding to the text subtitle stream. Alternatively, the palette

20 information may be included in the PCS information shown in FIG. 5A.

FIG. 6A illustrates a first example of the text subtitle decoder 42 shown in FIG. 4 according to the present invention, where a text subtitle stream is provided from an optical disc. The PCS information and ODS information included in a text subtitle stream preloaded in the subtitle preloading buffer (SPB) 41 may be initially arranged in the order of their information type and be stored in a coded data buffer (EB) 410. However, this process is only for improving an overall efficiency of the text subtitle decoder 42, and it may be omitted. Therefore, the coded data buffer 410 is only for optional and may not be included in the text subtitle decoding part 40 shown in FIG. 6A.

Referring back to FIG. 6A, a text subtitle processor (TXT\_ST parser) 411 included in the

text subtitle (TXT\_ST) decoder 42 parses the PCS and ODS information, which are preloaded in the subtitle preloading buffer (SPB) 41 or in the coded data buffer (EB) 410, into data representing a subtitle text (text data) to be included in a text subtitle region, inline style information, and region style information. When the PCS and ODS information are parsed by the text subtitle parser 411, the text data and the inline information are transferred to a text renderer 412 and the region style information is transferred to a composition buffer (CB) 414. Thereafter, the text renderer 412 renders the text data into bitmap data under control of a presentation (color/layout/composition) controller 415 using the region style information, the inline style information, and a font file. The font file may be extracted from an optical disc or a memory (not illustrated) included in the optical disc player 1 shown in

FIG. 1.

The composition buffer (CB) 414 stores the region style information parsed by the text subtitle parser 411 and provides this information to the presentation controller 415. An object buffer (DB) 413 temporarily stores the bitmap data outputted from the text renderer 412 and outputs the stored data according to time information (e.g., presentation time stamps). The presentation controller 415 controls operations of the text renderer 412 and the object buffer (DB) 413 according to the region style information, the inline style information, a corresponding clip information file, and a user input.

FIG. 6B illustrates a second example of the text subtitle decoder 42 shown in FIG. 4 according to the present invention, wherein a text subtitle stream is provided from an optical

disc. The text subtitle decoder 42 shown in FIG. 6B does not include an object buffer and a composition buffer. A text subtitle processor (TXT\_ST parser) 421 parses the text subtitle stream including PCS and ODS information into subtitle text data, inline style information, and region style information. When PCS and ODS information are parsed, the text data and inline style information are directly transferred to a text renderer 422 and the region style information is directly transferred to a presentation (color/layout/composition) controller 423. Thereafter, the text renderer 422 renders the text data into bitmap data under control of the presentation controller 423 using the region style information, inline style information, and a font file. The bitmap data is directly displayed through the graphics plane 43. Since the storing processes of the bitmap data and the region style information are omitted, the overall data process of the text subtitle decoder 42 is greatly simplified.

FIGs. 6C and 6D illustrate a third and fourth example of the text subtitle decoder 42 shown in FIG. 4 according to the present invention, where a text subtitle stream is provided from an external data source rather than from an optical disc. When a text subtitle stream includes data representing a subtitle text (text data) in XML or HTML format, the text data may include tag information (often referred to as "mark-up syntax") indicating property information of the text data. In the third example of the text subtitle decoder 42, pseudo-PCS (page composition segment) information and pseudo-ODS (object definition segment) information are created from the mark-up syntax. On the other hand, the mark-up syntax is ~~directly used when reproducing or decoding the text subtitle stream. For this reason, the~~

operations of the third and fourth examples of the text subtitle decoder 42 will be similar, in certain aspect, to those of the first and second examples shown in FIGs. 6A and 6B.

Referring to FIG. 6C, a text subtitle processor (TXT\_ST parser or segment converter) 431 included in the text subtitle decoder 42 converts a text subtitle stream originally provided from the external data source into standardized information. For example, if the text subtitle stream is in XML format, it initially converts the data into pseudo-PCS information and pseudo-ODS information including subtitle text data, and parses these information into the text data, inline style information, and region style information. When the pseudo-PCS and pseudo-ODS information are parsed, the text data and inline style information are transferred to a text renderer (a bitmap generator) 432, and the region style information is transferred to a composition buffer (CB) 434. Thereafter, the text renderer 432 renders the text data into bitmap data under control of a graphic controller 435 using the region style

information, the inline style information, and a font file. The font file may be extracted from an optical disc or a memory (not illustrated) included in the optical disc player 1 shown in FIG. 1.

The composition buffer 434 stores the region style information parsed by the text subtitle parser 431 and provides this information to the graphic controller 435. An object buffer (DB) 433 temporarily stores the bitmap data outputted from the text renderer 432 and outputs the stored data according to time information (e.g., presentation time stamps). The graphic controller 435 controls operations of the text renderer 432 and the object buffer 433 according to the region style information, the inline style information, a corresponding clip

information file, and a user input.

Referring to FIG. 6D, a text subtitle processor (TXT\_ST parser) 441 included in the text subtitle decoder 42 converts a text subtitle stream originally provided from the external data source into standardized information. For example, if the text subtitle stream is in XML or HTML format, it initially converts the data into pseudo-PCS information and pseudo-ODS information including subtitle-text data, and parses these information into the text data, inline style information, and region style information. When the pseudo-PCS and pseudo-ODS information are parsed, the text data and inline style information are transferred to a text renderer (442), and the region information style information is transferred to a graphic controller 443. Thereafter, the text renderer 442 renders the text data into bitmap data under control of the graphic controller 443 using the region style information, the inline style information, and a font file. The converted bitmap data is simultaneously displayed through

the graphics plane 43. Since the storing processes of the bitmap data and the region style information are not required, the overall data process of the text subtitle decoder 42 is greatly simplified.

FIG. 7 illustrates an apparatus of recording or reproducing text subtitle streams according to

5 the present invention. The apparatus shown in FIG. 7 includes a pickup unit 11 that reads AV streams and one or more text subtitle streams from an optical disc. The pickup unit 11 is also able to record AV streams and one or more text subtitle streams into an optical disc.

Each text subtitle stream being recorded on or read from the optical disc by the pickup unit

~~11 includes data representing a subtitle text (text data) to be displayed within a text subtitle~~

10 region of a display screen, region (global) style information specifying a region style of the text subtitle region including an overall font-related style of the text data, and inline (local) style information for applying a different font-related style to a selected portion of the text data.

The apparatus further includes a driver (e.g., a servo) 14 which controls operation of the  
15 pickup unit 11, a signal processor 13 which restores a signal received from the pickup unit 11 or modulates a signal into a recordable signal, a memory 15 which stores reproduction control information included in the text subtitle streams, and a microprocessor 16 which controls operations of the driver 14, the signal processor 13, and the memory 15.

The apparatus shown in FIG. 7 further includes an AV decoder 17 decoding the AV signal  
20 received from the signal processor 13, and an AV encoder 18 converting an input AV signal into a signal having a particular format, such as MPEG2 transport streams, and transmitting

the converted signal to the signal processor 13. In addition, the apparatus further includes a controller 12, which controls operations of the signal processor 13, the AV decoder 17, and the AV encoder 18.

5 **Industrial Applicability**

It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the spirit or scope of the inventions.

Thus, it is intended that the present invention covers the modifications and variations of this invention provided they ~~come within the scope of the appended claims and their equivalents.~~

Claims

1. A text subtitle decoder for decoding text subtitle streams recorded on a recording medium, comprising:

5 a text subtitle processor configured to parse a text subtitle stream into text data and reproduction control information, the text data representing a subtitle text to be displayed within a text subtitle region;

a text renderer configured to render the text data into bitmap data using the reproduction control information; and

10 a presentation controller configured to control operations of the text subtitle processor and the text renderer.

2. The text subtitle decoder of claim 1, wherein the text renderer further uses font data when rendering the text data into the bitmap data.

15

3. The text subtitle decoder of claim 1, further comprising:

a subtitle preloading buffer configured to preload an entire portion of the text subtitle stream from the recording medium, and to provide the preloaded text subtitle stream to the text subtitle processor.



4. The text subtitle decoder of claim 1, wherein the reproduction control information includes region style information specifying a region style of the text subtitle region including an overall font-related style of the text data.

5 5. The text subtitle decoder of claim 4, wherein the region style of the text subtitle region is specified by at least one of a region position, a region size, a region background color, a text position, a text flow, a text alignment, a line space, a font identification, a font style, a font size, and a font color defined in the region style information.

10 6. The text subtitle decoder of claim 4, wherein the overall font-related style of the text data is specified by at least one of a font identification, a font style, a font size, and a font color defined in the region style information.

15 7. The text subtitle decoder of claim 4, wherein the text subtitle processor configured to further parse the text subtitle stream into inline style information for applying a different font-related style to a selected portion of the text data.

20 8. The text subtitle decoder of claim 7, wherein the text data and the inline style information are transferred to the text renderer when the text subtitle processor parses the text subtitle stream.

9. The text subtitle decoder of claim 7, wherein the different font-related style is specified by at least one of a new font identification, a new font style, a new font size, and a new font color defined in the inline style information.

5

10. The text subtitle decoder of claim 7, wherein the selected portion of the text data comprises a text string.

11. The text subtitle decoder of claim 4, wherein the reproduction control information further includes palette information.

12. The text subtitle decoder of claim 1, further comprising:  
a composition buffer configured to store the reproduction control information parsed by the text subtitle processor, and to provide the stored information to the presentation controller.

15

13. The text subtitle decoder of claim 12, wherein the reproduction control information is transferred to the composition buffer when the text subtitle processor parses the text subtitle stream.

20

14. The text subtitle decoder of claim 1, further comprising:

an object buffer configured to store bitmap data outputted from the text renderer, and  
to output the stored bitmap data according to time information.

5

15. A method for decoding text subtitle streams recorded on a recording medium,  
the method comprising:

parsing a text subtitle stream into text data and reproduction control information, the  
text data representing a subtitle text to be displayed within a text subtitle region; and

10 rendering the text data into bitmap data using the reproduction control information.

16. The method of claim 15, further comprising:

preloading an entire portion of the text subtitle stream from the recording medium  
into a subtitle preloading buffer before the text subtitle stream is parsed.

15

17. The method of claim 15, wherein the reproduction control information includes  
region style information specifying a region style of the text subtitle region including an  
overall font-related style of the text data.

18. The method of claim 17, wherein the region style of the text subtitle region is specified by at least one of a region position, a region size, a region background color, a text position, a text flow, a text alignment, a line space, a font identification, a font style, a font size, and a font color defined in the region style information.

5

19. The method of claim 17, wherein the overall font-related style of the text data is specified by at least one of a font identification, a font style, a font size, and a font color defined in the region style information.

10

20. The method of claim 17, further comprising:

parsing the text subtitle stream into inline style information for applying a different font-related style to a selected portion of the text data.

15

21. The method of claim 20, wherein the different font-related style is specified by at least one of a new font identification, a new font style, a new font size, and a new font color defined in the inline style information.

22. The method of claim 20, wherein the selected portion of the text data is a text string.

20

23. The method of claim 17, wherein the reproduction control information further includes palette information.

24. The method of claim 15, further comprising:

5 storing the parsed reproduction control information in a composition buffer.

25. The method of claim 15, further comprising:

storing the bitmap data in an object buffer and outputting the stored bitmap data according to time information.

10

26. A system for decoding text subtitle streams recorded on a recording medium, the apparatus comprising:

a-text subtitle decoder configured to parse a-text subtitle stream into text data and reproduction control information, and to render the text data into bitmap data using the reproduction control information, the text data representing a subtitle text to be displayed within a text subtitle region;

a graphics plane configured to convert the bitmap data into displayable images; and

a color look up table configured to control at least one of color and transparency levels of the displayable images.

20

27. The system of claim 26, wherein the text subtitle decoder comprises:


a text subtitle processor configured to parse the text subtitle stream into the text data  
and the reproduction control information;

a text renderer configured to render the text data into the bitmap data using the  
5 reproduction control information and font data; and

a presentation controller configured to control operations of the text subtitle processor  
and the text renderer.


1/12

FIG. 1



2/12


FIG. 2A





3/12

FIG. 2B



4/12

FIG. 3A




FIG. 3B





FIG. 4



6/12

FIG. 5A


PCS information.

```
Page_Composition_Segment () {  
    segment_type  
    segment_length  
    composition_number  
    .....  
    composition_object () {  
        object_id  
        object_position_info  
        object_cropping_info  
        .....  
        (global) style_page  
    }  
}
```

e.g.,  
region\_position  
region\_size  
region\_background\_color  
text\_position  
text\_flow  
text\_alignment  
line\_space  
font\_id  
font\_style  
font\_size  
font\_color


7/12

FIG. 5B

ODS information


8/12

FIG. 6A




9/12

FIG. 6B



10/12


FIG. 6C






11/12

FIG. 6D



12/12

FIG. 7



## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/KR 2004/002598

## A. CLASSIFICATION OF SUBJECT MATTER

IPC<sup>7</sup>: H04N 7/00, 7/52

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC<sup>7</sup>: H04N 7/00, 7/52

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, PAJ, WPI

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 1326451 A1 (SONY CORPORATION) 9 July 2003 (09.07.2003) <i>abstract; [0031] - [0034]; claims; fig. 2.</i>	1,15,26,27
A	EP 0690335 A1 (DISCOVISION ASSOCIATES) 3 January 1996 (03.01.1996) <i>abstract; column 6, line 11 - column 8, line 16; claims; fig. 1.</i>	1,26
A	US 2003/0099464 A1 (YEONG-HEON OH et al.) 29 May 2003 (29.05.2003) <i>abstract; claims; fig. 1,2,3.</i>	1,26

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

## \* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&amp;" document member of the same patent family

Date of the actual completion of the international search  
28 April 2005 (28.04.2005)Date of mailing of the international search report  
11 May 2005 (11.05.2005)Name and mailing address of the ISA/ AT  
**Austrian Patent Office**  
Dresdner Straße 87, A-1200 ViennaAuthorized officer  
**ERBER H.**

Facsimile No. +43 / 1 / 534 24 / 535

Telephone No. +43 / 1 / 534 24 / 410

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/KR 2004/002598

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6204883-A (IKUO TSUKAGOSHI) 20 March 2001 (20.03.2001) <i>abstract; claims; fig. 1.</i> -----	1,5,6,19, 21

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR 2004/002598

Patent document cited in search report			Publication date	Patent family member(s)			Publication date
EP	A	690335		JP	A	8114858	1996-05-07
				EP	A1	0690335	1996-01-03
				CA	A1	2150099	1995-12-31
				AU	A	2010695	1996-01-18
EP	A	1326451		CN	A	1527606	2004-09-08
				AU	A	1842299	1999-04-29
				AU	B2	726256	2000-11-02
				CN	A	1139273	1997-01-01
				BR	A	9601263	1998-01-06
				US	A	5889564	1999-03-30
US	A	20030099 464		none			
US	B1	6204883	2001-03-20	US	A	5684542	1997-11-04
				JP	A	7231435	1995-08-29

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:**

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**